12.8 V SERIES · PRODUCT DATASHEET

PB128200

12.8 V 200 Ah LiFePO4 battery

RATED ENERGY
2.56 kWh

Twice the capacity of the PB128100 at the same voltage: 2.56 kWh for homes, small businesses and off-grid setups that need longer backup without re-wiring to a higher-voltage system.

NOMINAL VOLTAGE	CAPACITY	MAX DISCHARGE	MAX CHARGE
12.8 V	**200 Ah**	**750 W**	**60 A**

Specifications

Model	**PB128200**
Chemistry	**LiFePO4 (lithium iron phosphate)**
Nominal voltage	**12.8 V**
Rated capacity	**200 Ah**
Rated energy	**2.56 kWh**
Max. charging voltage	**14.4 V**
Max. charging current	**60 A**
Discharge cut-off voltage	**11.2 V**
Max. discharge power	**750 W**
BMS	**TriShield: BMS + fuse + MCB**
Monitoring	**Visual voltage & state-of-charge display**
Self-discharge	**max 3% per month**
Dimensions (L × W × H)	**365 × 250 × 240 mm (±20)**
Storage temperature	**25 °C**
Warranty	**3–5 years**

Key features

- TriShield — BMS + Fuse + MCB
- SCT — Sync Charge Technology: charge faster, last longer, stay safer
- SOC — visual voltage & state-of-charge monitoring
- High performance · Zero maintenance · Longer life

Ideal for

- Large home inverters
- Small shops and clinics
- Off-grid cabins and farms
- Long power cuts

TriShield protection: BMS (software: over-current, over-voltage, over-temperature and short-circuit protection), fuse and MCB (hardware: over-current and short-circuit protection). SCT Sync Charge Technology and visual voltage & state-of-charge monitoring. Do not connect batteries in series or parallel. Register the battery at powrio.com/warranty/register to receive a digital warranty certificate with QR verification. Specifications are subject to change; confirm with Powrio before ordering.

Powrio Energy Solutions · 310, Magnifico Commercial Hub, Thaltej, Ahmedabad, Gujarat 380054, India
1800-102-7251 (toll-free) · +91 96703 18958 · info@powrio.com · powrio.com