25.6 V SERIES · PRODUCT DATASHEET

PB256200

25.6 V 200 Ah LiFePO4 battery

RATED ENERGY
5.12 kWh

The highest-capacity 24 V pack in the range: 5.12 kWh and up to 2 kW discharge for larger solar arrays, business backup and critical loads on a 24 V system.

NOMINAL VOLTAGE	CAPACITY	MAX DISCHARGE	MAX CHARGE
25.6 V	**200 Ah**	**2000 W**	**80 A**

Specifications

Model	**PB256200**
Chemistry	**LiFePO4 (lithium iron phosphate)**
Nominal voltage	**25.6 V**
Rated capacity	**200 Ah**
Rated energy	**5.12 kWh**
Max. charging voltage	**29.2 V**
Max. charging current	**80 A**
Discharge cut-off voltage	**22.4 V**
Max. discharge power	**2000 W**
BMS	**TriShield: BMS + fuse + MCB**
Monitoring	**Visual voltage & state-of-charge display**
Self-discharge	**max 3% per month**
Dimensions (L × W × H)	**455 × 415 × 250 mm (±20)**
Storage temperature	**25 °C (±5 °C)**
Warranty	**3–5 years**

Key features

- TriShield — BMS + Fuse + MCB
- SCT — Sync Charge Technology: charge faster, last longer, stay safer
- SOC — visual voltage & state-of-charge monitoring
- High performance · Zero maintenance · Longer life

Ideal for

- Large 24 V solar arrays
- Business backup
- Critical-load circuits
- Whole-home essentials

TriShield protection: BMS (software: over-current, over-voltage, over-temperature and short-circuit protection), fuse and MCB (hardware: over-current and short-circuit protection). SCT Sync Charge Technology and visual voltage & state-of-charge monitoring. Do not connect batteries in series or parallel. Register the battery at powrio.com/warranty/register to receive a digital warranty certificate with QR verification. Specifications are subject to change; confirm with Powrio before ordering.

Powrio Energy Solutions · 310, Magnifico Commercial Hub, Thaltej, Ahmedabad, Gujarat 380054, India
1800-102-7251 (toll-free) · +91 96703 18958 · info@powrio.com · powrio.com